

FIBERLINK 20028

GPON OLT



DESCRIPTION

A GPON OLT with 8 ITU G.984 GPON compliant interfaces and 8 Gigabit Ethernet (GE) interfaces. Each PON port supports up to 64 ONUs (Optical Network Unit), totaling 512 GPON users, in addition to 8 point-to-point Ethernet connections. The Fiberlink 20028 GPON OLT is compact (1 RU - Rack Unit) and supports a full set of services and network topologies through its Ethernet ports.

The Fiberlink 20028 is a high performance OLT, developed to deliver ultra broadband services to a large number of users in a fast and cost-effective way.

The Fiberlink 20028 OLT is a third generation GPON equipment designed by Parks. Flexibility being one of its main features, this product can operate on GPON networks as well as on Metro Ethernet networks.

It presents functionalities that allow the management and development of the network, such as Link Aggregation (LACP), as well as IGMP protocol functionalities (for video streaming solutions). It features a redundant Hot-Swap power supply for 127/220VAC and/or -48VDC sources and can operate in optical redundancy – immediately going into operation in case of a fault in the network. It allows ring topology connection between up to 44 OLTs via RSTP or ERPS protocols.

Developed especially for the FTTH and Metro Ethernet services market, the Fiberlink 20028 is the ideal solution for both home and corporate applications.

HIGHLIGHTS

- ✓ GPON interfaces supporting extended reach of up to 60 km
- ✓ "Type B" redundancy of GPON interfaces for critical services.
- ✓ UPLINK of up to 20Gbits/s
- ✓ Up to 2 10GbE interfaces for ring topology creation
- ✓ ERPS (Ethernet Ring Protection Switching) protocol with sub-50ms recovery
- ✓ Complete provision through CLI or Parks NMS (graphic interface)
- ✓ Integrated Ethernet Switch with capacity for 108Gbit/s routing and MAC table of 32k addresses
- ✓ Advanced QoS mechanism in hardware, allowing L2 or L3 packet analysis (IPv4 and Ipv6)
- ✓ Support for 4096 simultaneous VLANs
- ✓ VLAN: hybrid mode port operation (QinQ and trunk simultaneously)
- ✓ PPPOE Intermediate Agent
- ✓ DHCP Relay Agent Information Option
- ✓ VLAN isolated function: Client isolation, even if belonging to the same VLAN
- ✓ Port bridging function: connectivity between clients, even if belonging to the same GPON port

TECHNICAL SPECIFICATIONS

INTERFACES

GPON INTERFACES

8 SFP GPON ITU-T G.984 Interfaces
1490nm downstream wavelength
1310nm upstream wavelength
Forward Error Correction (FEC) in upstream (US) and downstream (DS)
Upstream rate of 1.25 Gigabits/s
Downstream rate of 2.5 Gigabits/s
Downstream traffic protection through AES encryption with 128 bits key
Support for static and dynamic bandwidth allocation (SBA/DBA)
Reach of up to 20 km for each GPON interface (with up to 32 ONUs per GPON interface)
Support for extended reach of up to 60 km (with maximum window of 20 km)
Support for the 5 types of T-CONT (VoIP, IPTV, Management, Internet, Unspecified)
Up to 1024 GEM Ports per GPON interface
Up to 384 T-CONTs per GPON interface
Up to 64 ONUs per GPON interface

ETHERNET INTERFACES

Ethernet Switch with 8 slots for electrical or optical SFP modules
Ethernet Switch with up to 2 slots for 10 GbE SFP+ modules

MANAGEMENT AND SECURITY

Configuration through command line (CLI) and management system (Parks NMS) via SNMP
SNMP v2c, v3, and RFC1213
SNMP transport via UDP or TCP protocol
NTP client with support for multiple servers
Authentication via Radius and TACACS+ servers
In-band or out-of-band management (dedicated physical interface)
Remote management via SSH or Telnet secure protocol
Local and remote syslog
Firmware upgrade via FTP with support for two images to improve security
Access to the in-band management interface through specific and configurable VLAN (VID and CoS)
Supports configuration files import and export
SSH access with DSA keys mechanism
Off-line ONUs provision
Network protection through Link-Flap function, which disables ports with intermittent physical connection

FUNCTIONALITIES

LAYER 2 AND VLAN

Ethernet bridging with non-blocking architecture for all packet sizes

160Mpps (million packets per second) processing capacity

108Gbit/s commutation capacity

Flux control (IEEE 802.3x)

MAC address table with 32k entries

Support for 4095 VLANs

VLAN tagging via port, MAC, or Ethernet protocol (IEEE 802.1Q)

Q-in-Q VLAN (IEEE 802.1ad)

VLAN trunking and VLAN mapping

RSTP – Rapid Spanning Tree Protocol (IEEE 802.1w)

ERPS (Ethernet Ring Protection Switching) with sub-50ms recovery

DHCP Relay Agent Information Option (DHCP Relay Agent Option 82)

PPPoE Intermediate Agent (PPPoE tag)

LACP for dynamic aggregation of Ethernet ports

Support for L2 protocols transparency

Support for jumbo frames of up to 12000 bytes

IGMP Snooping v1/v2/v3

IGMP snooping with proxy reporting

IPTV streams forwarding

MAC Filtering

Port mirroring

Client isolation, even if they belong to the same VLAN (VLAN isolated)

Connectivity between clients, even if they belong to the same GPON port (port bridging)

Flexible ACLs (layer 2, 3, and 4) that can be defined by port or by VLAN

QoS

8 priority queues per physical

WRR or SP scheduling

Bandwidth control in ingress port

Bandwidth control in egress port

Traffic marking and classification

DSCP field remarking

CoS field remarking

DSCP Mapping à CoS through VLAN

MECHANICAL, ELECTRICAL AND ENVIRONMENTAL FEATURES

POWER SUPPLY

Two redundant sources with hot plugging (hot-swappable type)

DC power supply option with a -48 VDC (+ 25%) entry

AC power supply option with full-range entry (90~132VAC and 187~264VAC)

CONSUMPTION

Maximum 80W

ENVIRONMENT

0°C to 65°C (32°F to 149°F)

0 to 95% (non-condensing)

WEIGHT AND DIMENSIONS

W x H x D: 483 mm x 44 mm x 240 mm

19-inch mechanics and 1RU height

Lateral edges adjustable on installation

Weight: 3,6kg



For more information, visit www.parks.com.br.

The information presented in this document is subject to change without previous notice.