



germanengineering

BY 77 Video-Babyphone

Mit Sicherheit ein gutes Gefühl - Video-Babyphone für ruhige Stunden und sichere Nächte

ECO⁺ mode für eine strahlungsarme und energieeffiziente Übertragung

Digitale Wireless Technologie für eine hervorragende Bild- und Tonqualität

Videoüberwachung auch bei Dunkelheit durch Infrarot - Nachtsichtfunktion

Geräuschalarm

Temperaturalarm

Optische Geräuschpegelüberwachung durch leuchtende LEDs

Manuell schwenkbare Kamera

Reichweite von bis zu 300 Meter

Reichweitenkontrolle mit Signal bei Verbindungsabbruch

Digitale Zoomfunktion

Gegensprechfunktion

Batterieanzeige

Helligkeit und Lautstärke einstellbar

Störungsfreie Übertragung durch Verwendung mehrerer Kanäle

Monitor ist mit bis zu 4 Kameras kompatibel

5 sanfte Schlaflieder, von der Elterneinheit ab-/zuschaltbar

Übertragungsfrequenz 2,4 GHz

Inklusive Netzteile und Lithium-Ionen Akku für Elterneinheit

Elternteil sehr handlich dank einklappbarem Standfuß

Wandaufhängung für die Kamera

Netzteilspannung:

Eingang: 100-240 V AC / 50/60 Hz / 150 mA

Ausgang: 5 V micro USB, 600 mA

Produktmaße (inklusive Standfuß):

Elterneinheit (LxBxH): 11,5 x 6,9 x 2,4 cm

Kamera (LxBxH): 9 x 6,5 x 5,8 cm

Produktgewicht:

Elterneinheit: ca. 80 g (mit Clip)

Kamera: ca. 91 g

3 Jahre Garantie

VE: 4 / Transportkarton: -

EAN-Nr.: 4211125 95262 4

Art.Nr.: 952.62

BY 77 Baby video monitor

Provides peace of mind - baby video monitor for quiet hours and save nights

ECO⁺ mode: for low emissions and energy efficient transmission

Digital wireless technology for excellent picture and sound quality

Video surveillance also in the dark thanks to infrared night vision function

Sound alarm

Temperature alarm

Visual noise level monitoring with flashing LEDs

Rotating camera

Range of up to 300 m

Range control with signal when contact is interrupted

Digital zoom function

Intercom function

Battery indicator

Brightness and volume adjustable

Interference-free transmission with different channels

Compatible with up to 4 cameras

5 calming lullabies, can be switched off/on by the parent unit

Transmission frequency 2.4 GHz

Incl. mains part and Li-ion rechargeable batteries in the parent unit

Parent unit very handy thanks to retractable pedestal

Wall mounting for camera

Power supply voltage:

Input: 100-240 V AC / 50/60 Hz / 150 mA

Output: 5 V micro USB, 600 mA

Product measurements (including stand):

Parent unit (L x W x H): 11.5 x 6.9 x 2.4 cm

Camera (L x W x H): 9 x 6.5 x 5.8 cm

Product weight:

Parent unit: approx. 80 g (with clip)

Camera: approx. 91 g

3 year guarantee

Sales unit: 4 / Shipping unit: -

EAN no.: 4211125 95262 4

Item no.: 952.62