



A Tyco International Company

SENTRY DRY CHEMICAL HAND PORTABLE EXTINGUISHERS

Data/Specifications

FEATURES

- Economically priced
- Meets or exceeds requirements of ANSI/UL 299 and 711, or ULC S504 and S508
- USCG approved with proper bracket
- Simple operation and maintenance
- Tough, glare-resistant, one-piece mylar nameplates
- Rechargeable
- Manufactured of durable high quality materials
- Choice of dry chemical agents to satisfy specific protection requirements
- Large, easy-to-read pressure gauge
- Manuals, parts lists, videos available for training purposes
- Hand portable fire fighting training at the world renowned ANSUL Fire School
- Six-year limited warranty from date of delivery to original end-user purchaser
- Sold and serviced through an international network of independent distributors in every state and most foreign countries
- 2 1/2 and 5 lb units also available with vehicle bracket

APPLICATIONS

SENTRY dry chemical extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are suited for both industrial and commercial fire protection needs. All extinguishers are designed to fit most wall mounted storage cabinets. Typical applications include light manufacturing, warehousing, restaurants, office buildings, shop areas, auto repair shops, paint process areas, welding areas, machinery, apartment buildings, parking garages, aircraft servicing areas, material handling vehicles, and many others.

DESCRIPTION

1. SENTRY shells are produced by a cold deep draw process which yields a seamless steel cylinder with a high tensile strength.
2. Unique pre-treatment of the raw low carbon steel not only consists of a cleaning process, but also applies a special lubricant which helps keep the interior and exterior shell surfaces scratch free.
3. The collar and specially preformed bottom enclosure are MIG welded to produce a smooth, high integrity weld.
4. Extinguisher shells are 100% factory air tested in excess of 600 psi (41.4 bar).
5. The powder paint process is superior to conventional liquid based paint systems in its ability to resist blistering, cracking, fading, chipping and corrosion.
6. Before the extinguisher shells are painted, they are surface treated with a blasting or phosphate bonding process. This enhances the paint adhesion and corrosion resistance.
7. The specially formulated powder paint is electrostatically applied and oven cured to help ensure complete coverage and uniform paint thickness.
8. Easy grip extinguisher handles are designed for maximum portability, allowing operators to fight the fire without removing work gloves.
9. SENTRY extinguisher valve bodies are made from a durable extruded aluminum alloy.

10. Completed valve assemblies feature plated steel valve stems which contain O-Ring and seat material compatible with the agent to provide reliable performance and long life.
11. Rugged all-steel pick-up tubes help provide proper and dependable agent flow through the valve body.
12. Aluminum alloy hose ferrules are anodized to resist oxidation.
13. SENTRY extinguishers have large, color-coded pressure gauges which provide a quick visual indication of unit readiness.
14. Metal ring pins are utilized and held in place by a visual inspection seal to help prevent accidental discharges.
15. One piece, multilingual, color-coded mylar label with easy-to-read pictograms provides the user with step-by-step operating instructions and the hazard classes for which the extinguisher was designed. Label also contains useful recharge, maintenance, inspection, operating temperature, HMIS and model information.
16. Large, easy-to-scan bar coded model and UL/ULC serial numbers simplify inspection and maintenance record keeping.
17. Valve subassemblies are 100% tested for functionality before final assembly.
18. SENTRY extinguishers are vacuum-filled at the factory to precise filling tolerances.
19. Pressurized to 195 psi (13.4 bar), and 100% leak tested utilizing mass spectrometry technology.
20. Injection molded nozzle tips are designed to tight specifications and maximize the extinguishment capabilities of the particular model and agent.
21. SENTRY extinguishers are shipped from the factory in individual recyclable corrugated cardboard cartons. Designed and field tested to help assure your extinguishers arrive undamaged and ready for operation. The glued one-piece cartons have carrying handles and a pressure gauge inspection port.
22. All SENTRY extinguisher cartons are properly labeled according to the latest DOT regulations for ease of shipping in the field.
23. ANSUL dry chemical extinguishing agents are manufactured from the high quality raw materials and are carefully blended to meet stringent performance specifications. These agents are then tested to be free-flowing, water repellent and electrically nonconductive.
24. As a final quality control step, SENTRY extinguishers are randomly sampled for performance testing, which includes weight percent discharge and discharge times.

AGENT

FORAY – A monoammonium phosphate-based agent for use on Class A (wood, paper, cloth) and Class B (flammable liquids and gases) fires, and Class C (electrical) conductivity.





Purple-K – A potassium bicarbonate-based agent which is the most effective ANSUL agent for knock-down of Class B (flammable liquids and gases) fires, and Class C (electrical) conductivity.

PLUS-FIFTY C – A sodium bicarbonate-based agent for use on Class B (flammable liquids and gases) fires and Class C (electrical) conductivity.

ORDERING INFORMATION

For fire protection assistance, see your nearest authorized ANSUL distributor listed in your local yellow pages and at www.ansul.com; or contact your local ANSUL sales representative.

SPECIFICATIONS

Dry Chemical Extinguishers	SENTRY 2 1/2	SENTRY 5	SENTRY 10	SENTRY 20
				
	007101	007102	008403	007106
Model	A02VB	AA05-1/AA05VB-1	A05/A05VB	PK05
Extinguisher Part No. (except Canada) ¹	429101	434732/ 434735	429001/ 429102	429008 429102
Extinguisher Part No. (Canada) ²	429586	429587/ 429588	—	—
Bracket Part No.	24610	429146	429146	429146
Agent Capacity	2 1/2 lb (1.13 kg) FORAY	5 lb (2.27 kg) FORAY	5 lb (2.27 kg) Purple-K PLUS-FIFTY C	5 lb (2.27 kg) Purple-K PLUS-FIFTY C
UL/ULC Rating	1-A:10-B-C	3-A:40-B-C	3-A:10-B:C	60-BC
Coast Guard Classification	Type B, C, Size I	Type A, Size II Type B, C, Size I	Type A, Size II Type B, C, Size I	Type B, C, Size I
Discharge Time	9 seconds	14 seconds	17 seconds	14 seconds
Maximum Effective Range	11 ft (3.4 m)	14 ft (4.3 m)	16 ft (4.9 m)	16 ft (4.9 m)
Operating Temperature Range	-65 °F to 120 °F (-54 °C to 49 °C)	-65 °F to 120 °F (-54 °C to 49 °C)	-65 °F to 120 °F (-54 °C to 49 °C)	-65 °F to 120 °F (-54 °C to 49 °C)
Agent Flow Rate	0.31 lb/sec (0.14 kg/sec)	0.40 lb/sec (0.18 kg/sec)	0.36 lb/sec (0.16 kg/sec)	0.30 lb/sec (0.14 kg/sec)
Charged Weight (with agent)	5 lb (2.27 kg)	9 lb, 14 oz (4.15 kg)	9 lb, 14 oz (4.15 kg)	9 lb, 14 oz (4.15 kg)
Dimensions:				
Height	14 1/4 in (362 mm)	17 in (432 mm)	20 1/2 in (520 mm)	22 1/2 in (572 mm)
Width	5 1/2 in (140 mm)	8 1/2 in (216 mm)	8 1/4 in (210 mm)	9 1/2 in (241 mm)
Depth	3 3/8 in (86 mm)	4 7/16 in (113 mm)	5 1/4 in (135 mm)	7 7/32 in (183 mm)
Fire Suppression Capability ³ Operator: Experienced	10 ft ² (0.93 m ²) 25 ft ² (2.3 m ²)	40 ft ² (3.7 m ²) 100 ft ² (9.3 m ²)	10 ft ² (0.93 m ²) 60 ft ² (5.6 m ²) 150 ft ² (13.9 m ²)	80 ft ² (7.4 m ²) 150 ft ² (13.9 m ²) 200 ft ² (18.6 m ²)

1. UL Listed, English/Spanish nameplates.

2. ULC Listed, English/Canadian, French nameplates.

3. Underwriters Laboratories classifies a "novice operator" as one who has little or no experience in operating a fire extinguisher.

Approvals: DOT, USCG (All Models with proper bracket)

NOTE: VB denotes with vehicle bracket

Hydrostatic Test Requirement: Once every 12 years (All Models)

Operating Pressure: 195 psi (13.4 bar)