



HeartSine®

Inventor. Innovator. Lifesaver.

HeartSine samaritan® PAD 500P

With CPR Advisor



Defibrillation is easy, CPR is the hard part...

The HeartSine samaritan® PAD 500P provides all the advantages of the 300P with the addition of an innovative CPR advisor. Regardless of whether it is a lay person or a professional rescuer, the AHA/ERC guidelines place a greater emphasis on the importance of CPR and advocate the prompt initiation of effective bystander CPR to significantly reduce mortality due to out-of-hospital Cardiac Arrest (CA). HeartSine can now provide a device to support these guidelines by the introduction of the HeartSine samaritan PAD 500P with CPR Advisor.

Easy-to-follow Visual and Voice Prompts

Built-in confidence. The samaritan PAD 500P uses an Impedance Cardiogram (ICG) to assess the effectiveness of the CPR.

User-friendly. Easy-to-understand visual and voice prompts guide a user through the entire process.

Always ready. A System Status Ready Indicator flashes to show that the complete system is operational and ready for use. Device automatically runs self check each week.



Visual indicators let the user know if effective CPR is being administered.



Voice prompts let the user know if chest compressions are being given correctly. Aural "clicks" help the user keep time.

Compact in Size, Long on Ability

Durable. The samaritan PAD 500P resists shock and vibration and carries an IP56 Rating, the industry's highest rating against dust and moisture ingress. It also carries a 8-year unit warranty.

Advanced technology. The samaritan PAD 500P utilizes proprietary electrode technology, advanced and stable firmware, and proprietary SCOPE™* Biphasic Technology (an escalating and low-energy waveform that automatically adjusts for patient impedance differences) to assess rhythm and recommend defibrillation if necessary.



Advanced technology balanced against the demands of real world use. At HeartSine, our innovation changes lives. And saves lives.

Real Economy for the Real World

Two parts, one expiration date. Pad-Pak™ cartridge combines battery and electrode pads, with one expiration date to monitor.

Low cost of ownership. Cartridge has a shelf life of 4 years from date of manufacture, offering significant savings over other defibrillators that require separate battery and pad units.



Pad-Pak and Pediatric-Pak with pre-attached electrodes.

The HeartSine PAD's built-in intelligence and unique pediatric Pad-Pak ensure the appropriate energy level is delivered for children.



The CPR Advisor is deactivated when the Pediatric-Pak is in use.

*Self-Compensating Output Pulse Envelope technology automatically compensates energy, slope and pulse envelope for the patient.

| Physical | With Pad-Pak™ Inserted |
|----------|----------------------------------|
| Size: | 20cm x 18.4cm x 4.8cm |
| Weight: | 1.1 kg including Pad-Pak Battery |

| Defibrillator | |
|---------------|--|
| Waveform: | Self-Compensating Output Pulse Envelope Biphasic waveform. Optimized biphasic escalating waveform compensates energy, slope and envelope for patient impedance |

| Energy Selection | |
|------------------|---|
| Adult: | 1. Shock 150J 2. Shock 150J 3. Shock 200J |
| Pediatric: | 1. Shock 50J 2. Shock 50J 3. Shock 50J |

| Charging Time | |
|---------------------|--|
| New Battery: | Typically 150J in <8 sec., 200J in < 12 sec. |
| After 6 Discharges: | Typically 150J in <8 sec., 200J in < 12 sec. |

| Patient Analysis System | |
|--------------------------|---|
| Method: | Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required |
| Sensitivity/Specificity: | Meets ISO 60601-2-4 and AAMI DF80:2003 |

| Environmental | |
|---------------------------------------|--|
| Operating/Standby Temperature: | 0°C to 50°C (+32°F to +122°F) |
| Temporary Transportation Temperature: | -10°C to 50°C (14°F to 122°F) for up to two days. Unit must be returned to standby/operating temperature for 24 hours before use. |
| Relative Humidity: | 5% to 95% (non-condensing) |
| Water Resistance: | IEC 60529/EN 60529 IP56 |
| Altitude: | 0 to 15,000 feet (0 - 4,575 meters) |
| Shock: | MIL STD 810F Method 516.5, Procedure I (40G's) |
| Vibration: | MIL STD 810F Method 514.5+ Category 4 Truck Transportation - US Highways Category 7 Aircraft - Jet 737 & General Aviation (Exposure) |
| EMC: | EN 60601-1-2, Second Edition: 2002 |

| Environmental (continued) | |
|--------------------------------------|---|
| Radiated Emissions: | EN55011:2009 |
| Electrostatic Discharge RF Immunity: | EN61000-4-3:2007 80MHZ-2.5GHZ (10V/m) |
| Magnetic Field Immunity: | EN61000-4-8:2001 (3 A/m) |
| Aircraft: | RTCA/DO-160F, 2007, Section 21 (Category M) |
| Falling Height: | 1 meter |

| Event Documentation | |
|------------------------|---|
| Type: | Internal Memory |
| Memory Capacity: | 90 minutes of ECG (full disclosure) and event/incident recording |
| Playback Capabilities: | Custom USB cable directly connected to PC and Saver™ EVO Windows-based data review software |

| Materials Used | |
|----------------|--|
| PAD SAM300P: | ABS, Santoprene. Printed circuit board with electronic components. |
| PAD Cartridge: | Battery: Lithium Manganese Dioxide |
| Housing: | ABS - Electrodes: Hydrogel, Silver, Aluminium and Polyester |

| Pad-Pak – Electrode and Battery Cartridge | |
|---|---|
| Adult Pad-Pak (Pad-Pak-01) and Pediatric Pad-Pak (Pad-Pak-02) | |
| Shelf Life: | 4 years from manufacture date |
| Weight: | 0.44 lbs (0.2kg) |
| Size: | 3.93 in x 5.24 in x .94 in (10cm x 13.3cm x 2.4cm) |
| Battery Type: | Lithium Manganese Dioxide (LiMnO ₂) |
| Capacity: | Meets ISO 60601-2-4 and AAMI DF80:2003 18V, 1.5 Amp Hrs |
| Electrodes: | HeartSine samaritan® disposable defibrillation pads are supplied as standard with each device |
| Placement: | Anterior-lateral (Adult); Anterior-posterior (Pediatric) |
| Active Gel Area: | 100cm ² |
| Cable Length: | 3.5 ft (1m) |

Lifesaving, Pure and Simple

US/Americas

HeartSine Technologies, Inc.
121 Friends Lane, Suite 400
Newtown, PA. 18940
Toll Free: (866) 478 7463
Tel: (215) 860 8100
Fax: (215) 860 8192
info@heartsine.com

EMEA/ASP

HeartSine Technologies, Inc.
203 Airport Road West
Belfast, Northern Ireland BT3 9ED
Tel: +44 (0) 28 90 93 94 00
Fax: +44 (0) 28 90 93 94 01
info@heartsine.co.uk



The products described in this brochure all meet the applicable European Medical Directive requirements.

ISO 13485



HeartSine®

Inventor. Innovator. Lifesaver.

www.heartsine.com

© 2012 HeartSine Technologies, Inc.
All rights reserved. H009-014-025-0

MERT
EMERICAL SOLUTIONS. BUSINESS



HeartSine®

Inventor. Innovator. Lifesaver.

FREE Pad-Pak Program Helping Us Help You

The clinical information in event data contributes to product updates and fuels new product development activities. By downloading this data immediately following the use of the AED during a Sudden Cardiac Arrest, your contribution to these activities is immeasurable.



FREE Pad-Pak Rules

- ▶ After the use of the AED during a Sudden Cardiac Arrest (SCA), contact HeartSine to request a replacement Pad-Pak.
- ▶ Within 72 hours of the SCA, download the event data by following the instructions in the SAVER EVO manual or contact Technical Support (support@heartsine.com) for instructions on how to retrieve the data and forward it to HeartSine.
- ▶ To receive the free Pad-Pak, HeartSine must receive the data download within 72 hours of the AED being used.



It's Lifesaving, **Pure and Simple.**

MERT
EMERGENCY SOLUTIONS. BUSINESS

U.S./Americas

121 Friends Lane, Suite 400
Newtown, PA 18940
Toll Free: (866) 478 7463
Tel: +1 215 860 8100
Fax: +1 215 860 8192

Europe/Rest of World

203 Airport Road West
Belfast, Northern Ireland BT3 9ED
Tel: +44 28 90 93 94 00
Fax: +44 28 90 93 94 01

www.heartsine.com

H009-032-006-0