

# PLEXISTAB BULGARIA EAD

NEW

## MISSION:

"It's our mission to help you own your reinforced hose market"

## VISION:

### What?

We want to be the preferred supplier for our international client base.

### How?

By offering a complete assortment with high quality products, best in class service and a high level of professionalism in all aspects of our business.

### Why?

Through this approach we will reach a podium position in our markets and offer continuity and succes for our clients, employees and shareholders alike.

## WHY PLEXISTAB?

### Flexible

We are fast and effective problem solvers, flexible in our assortment and services in order to satisfy our clients' needs.

### Reliable

We are the reliable partner to our clients, offering on time and in full service, complimented by a pro-active attitude.

### Durable

We deliver quality products to our clients and build long lasting partnerships.



### Double Layer PVC Layflat Hose - Light Duty

**Structure:** Solid Black PVC inner wall, Polyester yarn reinforcement layer; Green PVC outer wall.

#### Applications:

1. Light duty water discharge hose in agriculture, civil engineering construction sites, on tank trucks, boats, ships.
2. Water delivery or supply of liquid fertilizers to surface irrigation systems and sprinklers at low working pressures.

#### Technical characteristics:

Working temp. range - 10°C to +60°C.



### Double Layer PVC Layflat Hose -Light/ Medium Duty

**Structure:** Solid Black PVC inner wall, Polyester yarn reinforcement layer; Orange PVC outer wall.

#### Applications:

1. Light/medium duty water discharge hose in agriculture, civil engineering construction sites and industrial sites.
2. Water delivery or supply of liquid fertilizers to surface irrigation systems and sprinklers at low/medium working pressures.

#### Technical characteristics:

Working temp. range - 10°C to +60°C.



### Double Layer PVC Layflat Hose -Medium Duty

**Structure:** Solid Black PVC inner wall, Polyester yarn reinforcement layer; Blue PVC outer wall.

#### Applications:

1. Medium duty water discharge hose in dewatering projects and industry.
2. Water delivery or supply of liquid fertilizers and other agricultural chemicals
3. Surface irrigation systems and sprinklers at medium working pressures.
4. Firefighting.

#### Technical characteristics:

Working temp. range - 10°C to +60°C.



### Double Layer PVC Layflat Hose -Heavy Duty

**Structure:** Solid Black PVC inner wall, Polyester yarn reinforcement layer; Red PVC outer wall.

#### Applications:

1. Heavy duty water discharge hose in dewatering projects, mining and industry.
2. Water delivery or supply of liquid fertilizers and other agricultural chemicals.

#### Technical characteristics:

Working temp. range - 10°C to +60°C.

