

Y-TYPE PLASTIC THREE WAY VALVE

Features & Specifications

- Designed for three hydraulic flow control positions.
- Common Port at base of the valve body.
- Base Port Thread: Male threaded $\frac{1}{4}$ " -19 BSP or $\frac{1}{4}$ "-18NPT
- Three Ports Thread: Female threaded $\frac{1}{8}$ " - 28 BSPT or $\frac{1}{8}$ " - 27 NPT
- Passage Size: 3.5mm
- Max. Pressure: 10 Bar/ 145Psi
- One moving part only.
- Three hydraulic control positions: Open, Close & Automatic.
- All valves are sealed when handle position in between port position.
- User friendly design allows smooth operation of handle with position indicator.
- All Plastic parts are Chemical/Corrosion resistant, Color UV stabilized.

New



Material

PART NO.	PART NAME	MATERIAL	QTY.
1	Base	PPGF/PBT	1
2	Base O-ring	EPDM/NBR	1
3	Stem O-ring	EPDM/NBR	2
4	Stem Seal	Teflon (PTFE)	3
5	Stem	PPGF/PBT	1
6	Body	PPGF/PBT	1
7	Body Cover	ABS/PPGF	1
8	Handle	ABS/PPGF	1
9	Screw	Stainless Steel	1



Dimensions (in mm)

D	L	L1	L2	H	H1
36.8	43	12.8	58	58.4	11

