

# ACG-751-PF

## FEATURES

- AISI-304 stainless steel exterior
  - AISI-304 stainless steel interior, stamped bottom, rounded corners and 24 press-formed supports for GN2/1 containers or shelves
  - Doors with self closing system, blocked opening, magnetic gasket, key lock as standard, possibility of changing the opening sense and inner side by stamped steel
  - LED lighting
  - AISI -304 adjustable legs, 135 to 200 mm
  - Hinged front control panel, easy access to the condenser unit
  - Monoblock refrigeration system:
  - Fan assisted condenser unit and evaporator, with epoxi anticorrosion coating
  - Automatic evaporation of defrost water
  - 40 Kg/m<sup>3</sup> density polyurethane insulation, zero GWP and zero ODP
  - Digital temperature control, optimized defrost, door open and hightemperature condensation alarms. Efficient management of energy consumption
- Operating ambient temperature 32°C



range 32°C 65Hr	W (mm)	D (mm)	H (mm)	frig. power (W)	capacity (L)	shelves (uds)	Voltage	Refrigerant
-20°C-15°C	645	800	2060	450 W	492	3	230 V - 50 Hz	R404A

## ACG-751-PF

Compressor	1/2 CV
Temperature Control	Electronic, with digital temperature display
Evaporator	Finned, Block Evaporator
Condensor	Finned, Block Condenser
Evaporator Fan	5 W
Condenser Fan	5 W
Refrigerant	R404A
Voltage	230 V / 50 Hz
Power consumption	840 W
Energy consumption (kW/24h)	11.46 Kw/24h
Energy label / EEI	G / 107.35
Insulation Material	Polyurethane
Foaming agent	C4H5F5
Insulation thickness	55 mm
Outer casing	AISI 304 Stainless Steel
Outside back	Galvanized steel
Innerliner	AISI 304 Stainless Steel
Door	Double glazed door with aluminium frame
Adjustable feet	4
Lighting	LED
Number of shelves	3
Min. shelf distance	55 mm
Shelf size (W x D)	530 x 650 mm (GN 2/1)

