



TSUDAKOMA
ROTARY TABLE
SELECTION GUIDE

OKK

ABOUT US


KOMA PRECISION

For over thirty years Koma Precision has been the foremost source for the finest the world has to offer in machine tool Productivity Innovation.

With over 30,000 rotary table installations, Koma is the largest distributor of Tsudakoma NC rotary tables and indexers in the world. With over 12,000 angle heads and live tools installed, Koma is the world's largest supplier for Alberti - the originator and the foremost innovator of productivity tooling.



ROTARY TABLES



RWE SERIES




RWA SERIES



RBS SERIES



RWB SERIES



RN-MULTI SERIES



TWA SERIES



TBS SERIES



5TH AXIS TILTING
RTT-111, CA

OKK VM SERIES

VM-43R				
RWE SERIES	RWE-160R	RWE-200R		
RWA SERIES	RWA-160R	RWA-200R	RWA-250R	
RBS SERIES	RBS-160	RBS-250		
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TWA-130			
TBS SERIES	TBS-130			
5 th AXIS TILTING	RTT-111, CA			
VM-53R				
RWE SERIES	RWE-200R			
RWA SERIES	RWA-200R	RWA-250R	RWA-320R	
RBS SERIES	RBS-250	RBS-320		
RWB SERIES	RWB-250R			
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TWA-130	TWA-160		
TBS SERIES	TBS-130	TBS-160		
5 th AXIS TILTING	RTT-111, CA			



VM-43R



VM-53R

OKK VM SERIES

VM-76R				
RWA SERIES	RWA-250R	RWA-320R		
RBS SERIES	RBS-250	RBS-320		
RWB SERIES	RWB-320R	RWB-400R		
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TWA-160	TWA-200		
TBS SERIES	TBS-160			
VM-660R				
RWA SERIES	RWA-250R	RWA-320R		
RBS SERIES	RBS-250	RBS-320		
RWB SERIES	RWB-250R	RWB-320R		
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TWA-130	TWA-160		
TBS SERIES	TBS-130	TBS-160		
5 th AXIS TILTING	RTT-111, CA			



VM-76R



VM-660R

OKK VM-940R & VP-600

VM-940R			
RWB SERIES	RWB-400R	RWB-500R	
TWA SERIES	TWA-200	TN-320	
5 th AXIS TILTING	RTT-111, CA		
VP-600			
RWA SERIES	RWA-250R	RWA-320R	
RBS SERIES	RBS-250	RBS-320	
RWB SERIES	RWB-250R	RWB-320R	
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4
TWA SERIES	TWA-160	TWA-200	
TBS SERIES	TBS-160		



VM-940R



VP-600

OKK KVC SERIES

KCV-800				
RWB SERIES	RWB-320R	RWB-400R		
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TWA-200	TN-320		
KCV-1000				
RWB SERIES	RWB-250R	RWB-320R		
RN MULTI SERIES	RN-100R-2	RN-100R-3	RN-100R-4	
TWA SERIES	TN-320			




KCV-800




KCV-1000

ROTARY TABLE DIMENSIONS


VM-43R




VM-53R
Type B




VM-53R
Type C




VM-76R




VM-940R




VM-660R




VP-600



KCV-800







KCV-1000



ROTARY TABLE DIMENSIONS





RWE, RWA, & RBS-Series ROTARY TABLE DIMENSIONS (Drawings Not To Scale)

RWE-160







RWE-200

RWA-160




RWA-200

RWA-250





RWA-320



RBS-160



RBS-250



RBS-320




Please contact Koma Precision to confirm OKK / Tsudakoma Rotary Table working envelope.

www.komaprecision.com • info@komaprecision.com • 1-800-249-5662


ROTARY TABLE DIMENSIONS

RN-Multi, RTT-111 CA & RWB-Series ROTARY TABLES (Drawings Not To Scale)


RWB-250R




RWB-320R




RWB-400R




RWB-500R



RTT-111, CA



RN-100,R-2,3,4





Please contact Koma Precision to confirm OKK / Tsudakoma Rotary Table working envelope.

www.komaprecision.com • info@komaprecision.com • 1-800-249-5662



ROTARY TABLE DIMENSIONS

TWA & TBS-Series ROTARY TABLE DIMENSIONS (Drawings Not To Scale)



TWA-130





TWA-160





TWA-200





TN-320



TBS-130



TBS-160



Please contact Koma Precision to confirm OKK / Tsudakoma Rotary Table working envelope.

www.komaprecision.com • info@komaprecision.com • 1-800-249-5662

ROTARY TABLE SPECIFICATIONS

RWE & RWA-Series Rotary Tables

Table Model		RWE-160	RWE-200	RWA-160	RWA-200	RWA-250 (S)	RWA-320 (S)
Versions available		R, L	R, L	R, L	R, L	R, L	R, L
Spindle outer diameter		100h7	120h7	100h7	120h7	140h7	180h7
Table diameter (optional)		(160, 200)	(200, 250)	(160, 200)	(200, 250)	250	320
Center height		135	160	135	160	160	210
Center bore	Nose Diameter	55H7	65H7	55H7	65H7	80H7	115H7
	Thru Diameter	40	45	40	45	50	85
Table T-slot width (with faceplate)		(12H8)	(12H8)	(12H8)	(12H8)	12H8	14H7
Guide block width		14h7	18h7	14h7	18h7	18h7	18h7
Servo motor (Fanuc)*		Alpha 2i	Alpha 4i	Alpha 2i	Alpha 4i	Alpha 8i (8is)	Alpha 8i (22is)
Maximum motor speed	rpm	5,000	5,000	5,000	5,000	4,000 (4,000)	4,000 (3,000)
Speed reduction ratio		1/72	1/72	1/72	1/72	1/90 (1/45)	1/120 (1/45)
Maximum table speed	rpm	69.4	69.4	69.4	69.4	44.4 (88.9)	33.3 (66.6)
Inertia converted into motor shaft	x 10 ⁻³ kg·m ²	.09	.17	.09	.17	.41 (.44)	.52 (1.66)
Clamp system		Pneumatic Disc Clamp		Pneumatic Dual Taper			
Clamp torque @72psi	Nm (ft. lbs.)	250 (180)	400 (295)	500 (369)	800 (590)	1,000 (737)	1,500 (1,106)
Indexing accuracy	arc sec.	±12.5	±10	±12.5	±10		
Net Weight	kg (lbs.)	40 (88)	61 (135)	38 (84)	61 (134)	80 (176)	145 (319)
Allowable wheel torque	Nm (ft. lbs.)	206 (152)	288 (212)	206 (152)	288 (212)	596 (439)	939 (692)
Allowable work inertia	kg·m ²	.64	1.25	.64	1.25	1.95	4.48
Allowable work weight	 kg (lbs) [w/ tailstock]	100 (220) [200 (441)]	125 (275) [250 (551)]	100 (220) [175 (385)]	125 (275) [250 (550)]	125 (275) [250 (550)]	175 (385) [375 (825)]
	 kg (lbs)	-	-	200 (440)	250 (550)	250 (550)	350 (770)
Allowable load when table clamped	 N (lbf)	10,800 (2,419)	14,400 (3,226)	10,800 (2,419)	14,400 (3,226)	14,400 (3,226)	24,800 (5,555)
	 Nm (ft. lbs.)	500 (369)	800 (590)	500 (369)	800 (590)	1,000 (737)	1,500 (1,106)
	 Nm (ft. lbs.)	780 (575)	1,900 (1,400)	780 (575)	1,900 (1,400)	1,900 (1,400)	4,700 (3,464)

* Other motors & RPM available

** Booster optional

Dimensions = mm

Specifications subject to change without notice

ROTARY TABLE SPECIFICATIONS

RN-Multi, RBS & RWB-Series Rotary Tables

Table Model		RN-100-2,3,4	RBS-160	RBS-250	RBS-320	RWB-250	RWB-320	RWB-400	RWB-500
Versions available		R, L	R	R	R	R, L	R, L	R, L	R, L
Spindle outer diameter		80h7	100h7	140h7	180h7	-	-	-	-
Table diameter (optional)		(135)	(160, 200)	250	320	250	320	400	500
Center height		110	160	210	255	160	210	255	310
Center bore	Nose Diameter	50H7	55H7	80H7	115H7	105	150	200	220
	Thru Diameter	30	40	50	85	80	120	160	182
Table T-slot width (with faceplate)		10H8	12H8	12H8	14H8	12H7	14H7	14H7	18H7
Minimum spindle center distance		120	-	-	-	-	-	-	-
Guide block width		14h7	14h7	18h7		18h7			
Servo motor (Fanuc)*		Alpha 2i	Alpha 4i	Alpha 8i	Alpha 12i	Alpha 8i	Alpha 12i	Alpha 12i	Alpha 12i
Maximum motor speed	rpm	5,000	5,000	4,000	4,000	4,000	4,000	4,000	4,000
Speed reduction ratio		1/36	1/36	1/36	1/36	1/90	1/90	1/90	1/180
Number of spindles		2 3 4	-	-	-	-	-	-	-
Maximum table speed	rpm	83.3	138.9	111.1	111.1	44.4	44.4	44.4	22.2
Inertia converted into motor shaft	x 10 ⁻³ kg·m ²	.64 .92 1.06	.19	0.42	2.24	1.27	3.53	4.63	3.00
Clamp system		Pneumatic		Pneumatic		Hydraulic			
Clamp torque	Nm (ft. lbs.)	80 (59)	700 (516)	1480 (1076)	2580 (1901)	1,300 (958)	3,100 (2,284)	5,500 (4,053)	6,100 (4,496)
Indexing accuracy	arc sec.	±22.5	±12.5	±7.5		±7			
Net Weight	kg (lbs.)	28 (62)	44 (97)	100 (220)	200 (440)	125 (286)	250 (550)	360 (792)	620 (1,364)
Allowable wheel torque	Nm (ft. lbs.)	176 (130)	206 (152)	288 (212)	596 (439)	1,011 (745)	2,127 (1,567)	3,958 (2,917)	3,276 (2,414)
Allowable work inertia	kg·m ²	.10	.48	1.95	4.48	7.0	19.2	36	112
Allowable work weight	 kg (lbs) [w/ tailstock]	25 (55) [50 (110)]	75 (165) [150 (330)]	125 (275) [250 (550)]	175 (385) [350 (770)]	385 (175) [770 (350)]	550 (250) [1,100 (500)]	660 (300) [1,320 (600)]	1,320 (600) [2,460 (1,200)]
	 kg (lbs)	50 (110)	-	250 (550)	350 (770)	770 (350)	1,100 (500)	1,320 (600)	2,640 (1,200)
Allowable load when table clamped	 N (lbf)	5,880 (1,317)	7,840 (1,762)	14,400 (3,226)	24,800 (5,555)	35,000 (7,700)	89,000 (19,580)	109,000 (23,980)	240,000 (52,800)
	 Nm (ft. lbs.)	80 (59)	250 (180)	1,000 (737)	1,500 (1,106)	1,300 (958)	3,100 (2,284)	5,500 (4,053)	7,600 (5,601)
	 Nm (ft. lbs.)	156 (115)	392 (290)	1,900 (1,400)	4,700 (3,464)	1,500 (1,105)	5,300 (3,906)	7,800 (5,748)	17,000 (12,529)

* Other motors & RPM available



** Booster optional

Dimensions = mm

Specifications subject to change without notice

ROTARY TABLE SPECIFICATIONS


TWA-Series Rotary Tables

Model			TWA-130		TWA-160		TWA-200		TN-320	
Tilt Range			-17° ~ +107°		-30° ~ +110°		-30° ~ +110°		-30° ~ +110°	
Spindle outer diameter			90h7		100h7		120h7		-	
Table diameter (optional)			(135)		160 (200)		200 (250)		320	
Table height at 0° position			210 (235 w/faceplate)		235 (260 w/faceplate)		270 (300 w/faceplate)		355	
Center height at 90° position			150		180		210		255	
Center bore	Nose Diameter (w/face plate)		55H7 (40H7)		55H7 (50H7)		65H7 (60H7)		105H7	
	Thru Diameter		35		40		45		100	
Table T-slot width			12H8 (w/faceplate)		12H8 (w/faceplate)		12H8 (w/faceplate)		14H7	
Guide block width			14h7		18h7		18h7		18h7	
Servo motor (Fanuc)*			Rotary	Tilt	Rotary	Tilt	Rotary	Tilt	Rotary	Tilt
			Alpha 2i	Alpha 2i	Alpha 2i	Alpha 2i	Alpha 4i	Alpha 4i	Alpha 8i	Alpha 8i
Maximum motor speed	rpm		5,000	5,000	5,000	5,000	5,000	5,000	4,000	4,000
Speed reduction ratio			1/60	1/120	1/72	1/120	1/45	1/90	1/120	1/240
Maximum table speed	rpm		83.3	41.7	69.4	41.7	111.1	55.5	33.3	16.6
Inertia converted into motor shaft	x 10 ⁻³ kg.m ²		.074	.072	.17	.18	.38	.45	.82	.45
Clamp system			Pneumatic Dual Taper						Hydraulic @500 psi **	
Clamp torque @72psi		Nm (ft. lbs.)	500 (369)	500 (369)	500 (369)	800 (590)	800 (590)	1,000 (737)	[2,200] [(1,621)]	[2,200] [(1,621)]
Indexing accuracy		arc sec.	±20	-	±15	-	±15	-	±10	-
Tilting accuracy		arc sec.	-	±22.5	-	±22.5	-	±22.5	-	±22.5
Net Weight		kg (lbs.)	76 (167)		127 (279)		190 (418)		440 (968)	
Allowable wheel torque - rotary		Nm (ft. lbs.)	152 (112)		200 (147)		450 (332)		931 (686)	
Allowable work inertia		kg.m ²	.08		.19		.59		1.53	
Allowable work weight	0° tilt angle 	kg (lbs)	35 (77)		60 (132)		120 (264)		150 (330)	
	0° ~ 90° tilt angle 	kg (lbs)	20 (44)		40 (88)		70 (154)		100 (220)	
Allowable work moment		Nm (ft. lbs.)	24 (17.7)		39.2 (28.9)		53.7 (39.6)		163.3 (120.4)	
Allowable load when table clamped		N (lbf)	3,920 (878)		7,840 (1,756)		13,720 (3,073)		19,600 (4,390)	
		Nm (ft. lbs.)	500 (369)		500 (369)		800 (590)		2,200 (1,621)	
		Nm (ft. lbs.)	500 (369)		800 (590)		1,000 (737)		2,200 (1,621)	


* Other motors & RPM available • ** Booster optional • Dimensions = mm • Specifications subject to change without notice

ROTARY TABLE SPECIFICATIONS

TBS-Series & RTT-111, CA Rotary Tables

Model		TBS-130		TBS-160		RTT-111, CA	
Tilt Range		-30° ~ +110°		-30° ~ +110°		-17° ~ +107°	
Spindle outer diameter		90h7		100h7			
Table diameter (optional)		(135)		(160 or 200)			
Table height at 0° position		225 (250 w/faceplate)		270 (300 w/faceplate)		190	
Center height at 90° position		160		200		190	
Center bore	Nose Diameter (w/face plate)	55H7 (40H7)		55H7 (50H7)		--	
	Thru Diameter	40		40		--	
Table T-slot width		12H8		12H8		--	
Guide block width		14h7		18h7		14H7	
Servo motor (Fanuc)*		Rotary	Tilt	Rotary	Tilt	Rotary	Tilt
		Alpha 2i	Alpha 2i	Alpha 2i	Alpha 4i	Alpha 2i	Alpha 2i
Maximum motor speed	rpm	5,000	5,000	5,000	5,000	5,000	5,000
Speed reduction ratio		1/48	1/60	1/60	1/60	1/60	1/120
Maximum table speed	rpm	104.2	83.3	83.3	83.3	83.3	41.7
Inertia converted into motor shaft	$\times 10^{-3} \text{kg} \cdot \text{m}^2$	.074	.072	.17	.18	.074	.072
Clamp system		Pneumatic				Pneumatic Dual Taper	
Clamp torque @72psi	Nm (ft. lbs.)	700 (516)	700 (516)	700 (516)	700 (516)	500 (369)	500 (369)
Indexing accuracy	arc sec.	±10	-	±10	-	±20	-
Tilting accuracy	arc sec.	-	±17.5	-	±17.5	-	±30
Net Weight	kg (lbs.)	125 (276)		160 (353)		98(216)	
Allowable wheel torque - rotary	Nm (ft. lbs.)	-		-		152(112)	
Allowable work inertia		.08		.19		.08	
Allowable work weight	0° tilt angle 	kg (lbs)	35 (77)	60 (132)	35 (77)		
	0° ~ 90° tilt angle 	kg (lbs)	20 (44)	40 (88)	20 (44)		
Allowable work moment		Nm (ft. lbs.)	61.1	59.6	57 (42)		
Allowable load when table clamped		N (lbf)	3,920 (878)	10,800	3,920 (878)		
		Nm (ft. lbs.)	700 (516)	700 (516)	500 (369)		
		Nm (ft. lbs.)	700 (516)	700 (516)	500 (369)		

* Other motors & RPM available • Dimensions = mm • Specifications subject to change without notice



Tsudakoma-OKK 19.0 1/15/19



Tel: 1.800.249.5662
Fax: 860.623.4132

info@komaprecision.com
www.komaprecision.com

20 Thompson Road
East Windsor, CT 06088

