

Keks

Light-meters designed for
analogue cameras.

KEKS

Making your photographic experience easier and more enjoyable than ever before.

Introducing the KM-Q and KM02 OLED light-meters. Including ground-breaking new features, compact dimensions and outstanding performance.



Applicable to more cameras

Both the KM-Q and KM02 come with 3 different sizes of hot shoe mounts allowing them to be fitted onto virtually any camera with ease.

Long life battery

Powered by built-in batteries which are recharged using a TYPE-C charging port.

This allows continuous user operation for up to 20 hours for the KM-Q and 21 hours for the KM02.

Quality materials & elegant design


The sleek and elegant designs and manufactured using high-quality aluminium.

Available in black or chrome finish to blend in perfectly with your classic camera's timeless design.

capix

+44 (0) 1480 472233
info@capix.com
www.capix.com

Unit 1, Woodbine Farm,
Oundle Road, Lutton,
Northamptonshire, PE8 5ND, UK



Keks

Light-meters designed for analogue cameras.

KEKS

KM02

The new KM02 OLED light-meter includes ground-breaking new features, compact dimensions and outstanding performance, making your photography experience easier and even more enjoyable.

Operation couldn't be more straight-forward with the KM02 the user is able to switch between aperture priority and shutter priority mode at the simple flick of a button.



KM-Q

The KM-Q sugar cube-sized ultra-compact OLED light-meter redefines portability, and positioning. It is the most compact model in the line-up. Just half the size of the KM02, the KM-Q still inherits the same exceptional build quality and outstanding performance.

Available in both top and back display versions to cater for the diverse needs of film photography enthusiasts.



Technical specification

	KM02	KM-Q		KM02	KM-Q
Material:	Aluminium	Aluminium	Monitor:	0.91" OLED	0.42" OLED
Colours:	Black or Chrome	Black or Chrome	Metering:	30° av. metering (approximately 50mm lens view)	30° av. metering (approximately 50mm lens view)
Shoe mounts:	3x sizes shoe mount	3x sizes shoe mount	Aperture value:	F/1.0-F/128	F/1.0-F/64
Dimensions:	42.0x27.0x15.5mm	21x25.5x22mm	Shutter speed:	30s-1/8000	1/6400s to 30s
Weight:	29g	18.5g	ISO value	6-102400	50-80000
Battery:	220mAh (2.5h charging time)	120mAh (30min charging time)	Metering mode:	Single / Continuous	Single / Continuous
Battery life:	21hrs (Always On Display)	20hrs (Always On Display)	Exposure mode:	Aperture / Shutter Priority	Aperture / Shutter Priority
Charging Port:	USB Type C	USB Type C			

capix

+44 (0) 1480 472233
info@capix.com
www.capix.com

Unit 1, Woodbine Farm,
Oundle Road, Lutton,
Northamptonshire, PE8 5ND, UK

