

AnTech®



Type F, Wellhead Outlets, Fiber

Ensuring safe connections for wellhead interfaces with fiber optic feedthroughs

With increasing demands for more data and operating at higher temperatures, there has been a growth in use of fiber optic cables for permanent monitoring. These solutions are only as good as the connections at surface and the AnTech Type F Wellhead Outlet range has been designed specifically to meet this need whilst maintaining the highest safety standards.

The adoption of fiber optics by the petroleum industry has created new demands for equipment that can safely allow fiber optic connections to downhole gauges in high temperature and pressure environments.

With the advancement in sensor technology the connections at surface also needed to evolve as standard connectors are not sufficient. AnTech have developed their own feedthroughs for fiber outlets and can offer a number of connection types including fusion splicing and mechanical connectors, suitable for operating temperatures up to 150°C and 15,000 psi.

The Type F outlets incorporate systems for storing excess fiber so that multiple attempts can be made at connecting the fiber, whilst protecting the delicate fiber.

The units share the same high levels of quality that all AnTech's outlets are known for and are designed and tested to meet the specifications set out in API 6A. Additional options are available such as PR2 and PSL 3G ratings. AnTech's design allows for pressure testing upon installation to ensure seals are pressure testable.



AnTech's flexible approach means that it can deliver bespoke and standard fiber outlet solutions for most wellhead connections and downhole cables.

Features & Benefits

- Bespoke and standard models available
- High pressure ratings available
- Designed for use in hazardous areas
- Simple and easy installation
- Ability to pressure test upon installation



For information on our electrical ranges please visit our website



AnTech Ltd, Unit 7, Newbery Centre, Airport Business Park, Exeter, EX5 2UL, U.K.

T: +44 1392 933 100 sales@antech.co.uk | ctd@antech.co.uk

www.antech.co.uk | www.coiledtubingdrilling.com | www.gyrosurveys.com

Offices also in the USA and Middle East | © AnTech Ltd 2017. All rights reserved.

Technical Specifications for our Type F Wellhead Outlet Range

Product		Type FA	Type FB	Type FC
Connection Type		Flanged or threaded connections as per customer requirements		0.5" NPT (10kpsi), 1.0" NPT (5kpsi), 1.5" NPT (5kpsi), 1" Autoclave (10kpsi)
Working Pressure		Up to 15,000 psi / 103 MPa		
API6A/ISO10423 Rating		-20°C ≤ T ≤ 150°C FF-NL PSL 3 Other options available: PR2 and PSL 3G	-20°C ≤ T ≤ 150°C FF-NL PSL 3 Other options available: PR2 and PSL 3G	-20°C ≤ T ≤ 100°C FF-NL PSL 3 Other options available: PR2 and PSL 3G
API6FB		N/A	As standard. Tested To API 6FB Part 2 (Offshore, Non Bending).	N/A
ATEX/IECEX Rating		Safe to use in all hazardous areas as power use is below ATEX limitations.		
Ambient Temperature		°C	-20 °C to +150 °C	-20 °C to +150 °C
		°F	-4 °F to +302 °F	-4 °F to +302 °F
Secondary barrier method		Metal to Epoxy		Metal to Epoxy
Compatible lines		Single-, Dual-, Triple-, Quad-Fibre	Single-fibre or Dual-fibre	Single-, Dual-, Triple-, Quad-Fibre
Maximum power		35 mW		35 mW
Number of barriers		2		2
Ingress protection		IP54 (min)		
Ability to pressure test upon installation		Yes		
Sour Service**		As standard		
CO2 Service		If requested		
Acid Service		If requested		
Approximate Dimensions	Length	428 mm / 18.942 in	428 mm / 18.942 in	580 mm / 22.84 in
	Diameter	140 mm / 5.500 in	145 mm / 5.710 in	56.5 mm / 2.22 in

*Customer line type dependent, **In compliance with NACE MR 00175/ISO 15156