

aquamax KF

SWOP Box

Universal reagent exchange module

Product description

The SWOP BOX makes it easy to change reagents in titration cells easily and conveniently. The module can be used e.g. on any Karl Fischer titrator of any design, if the titration cell has at least one free connection.

The two bottles for the reagent supply and for the used solution have each a capacity of 500 mL or 1000 mL.

The reagent exchange module is battery operated. The internal Li-ion batteries can be easily recharged.

Applications

The system can be used for all types of liquid samples, including aggressive media and solvents, but not for highly viscous substances.



View of the back

Simple reagent exchange

The emptying and filling of the measuring cell is controlled by the rotary knob, which activates the pump. The maximum flow rate is 150 mL/min.

This means that changing 130 mL of reagent takes less than a minute. There is no need for cumbersome disassembly of the measuring cell.

Features

- Quick reagent change without dismantling of the titration cell
- Can be connected to all Karl Fischer titrators, no matter from which manufacturer
- Chemically resistant pump (150 mL/min)
- Independent of power supply due to integrated rechargeable battery
- Carrying handle for easy transport

Device variants

aquamax KF SWOP Box



Variant:	SWOP Box
Operation:	Manual
Mains:	7.4 V DC or battery
Bottle volume for reagent:	500 or 1000 mL
Bottle volume for waste:	500 or 1000 mL
Protection class:	IP 20

aquamax KF SWOP Box PRO



Variant:	SWOP Box PRO
Operation:	Automatic
Mains:	12 V DC
Bottle volume for reagent:	500 or 1000 mL
Bottle volume for waste:	500 or 1000 mL
Protection class:	IP 20

Technical specifications

Capacity:	2 bottles with 500 or 1000 mL each (\varnothing max. 85 mm)	
Pump:	150 mL/min, chemical resistant	
Power supply:	External charger LiMH battery 7 V (2600 mA/h), charge level indicator	
Dimensions:	Carrying handle set up:	180 x 225 x 260 mm (W x D x H)
	Carrying handle folded down:	180 x 225 x 180 mm (W x D x H)
Weight:	Approx. 1.2 kg	

ECH Elektrochemie Halle GmbH

Otto-Eißfeldt-Str. 8
D-06120 Halle (Saale)
Germany

Tel.: +49 (0) 345 279570-0
Fax: +49 (0) 345 279570-99

Email: info@echscientific.com • www.ech.de • www.aquamaxkf.com

ECH Scientific Limited

Building 69, Wrest Park, Silsoe
Bedfordshire, MK45 4HS
United Kingdom

Tel.: +44 (0) 1525 404747
Fax: +44 (0) 1525 404848



SCIENTIFIC
part of ECH Elektrochemie Halle
Global Sales Division

the ECH advantage

in-lab | mobile | on-line | process