

## A New Matte Option for Your Hard Surfaces

### MICROGUARD1<sup>®</sup> MATTE

Extends Asset/Property Life

Non-Yellowing Matte Finish

Long-Term Durability (ASTM D-4060)

Mitigates Microbial Growth (ASTM G-21)

Chemical and Stain Resistant

Non-Sacrificial, Anti-Graffiti

Hydrophobic

9H hardness

Can Be Repaired and Recoated

Low Maintenance, Easy to Clean

Verifiable ROI



### *A Matte Finish with Adsil Attitude!*

With a single-layer and single-application, MicroGuard1<sup>®</sup> Matte (MG-MT) provides a beautiful, hydrophobic, anti-microbial matte finish that's Adsil Strong and is easy to mix, apply, and clean.

MicroGuard1<sup>®</sup> Matte is an additive that combines with our stock MicroGuard1<sup>®</sup> 1500 coating without affecting performance. That means you get a gorgeous matte finish with all of Adsil's proven benefits. No new coating to stock – just order the additive when you need it.

- Average gloss meter reading after MicroGuard1 Matte application is 7-15 (depending on original substrate)
- Architects and specifiers requiring a matte finish can now be accepted
- Can be stripped, repaired and recoated

Our proprietary, clear siloxane coating covalently bonds with your surface to produce a strong, thin finish that delivers remarkable long-term protection and wear-resistance – inside or out – all with a beautiful matte finish. That means no corrosion, abrasive wear, mold, odor, graffiti or chemical attack. It also means reduced maintenance and cleaning costs.

Call **386-274-1382** to preserve, prolong and protect your most valuable assets, and your bottom line, with MicroGuard1<sup>®</sup> today!


## Preserve

Interrupt the expensive replacement cycle by preserving your hard surfaces so they last longer and are easier to clean.



## Prolong

Extend the life of your assets, inside and outside, with sustainable results and a verifiable ROI.



## Protect

Proven, professional-grade protection stains, abrasion, corrosion, UV light, graffiti and microbial growth.



## SPECIFICATIONS

<b>Type</b>	Proprietary additive designed for use with MicroGuard1® 1500
<b>Application Method</b>	Paint pan or pump-up sprayer, then back-roll with high quality 3/8" microfiber roller
<b>Thinner</b>	None
<b>Clean Up</b>	MicroKleen™ AD1-919
<b>Dry Time w/MG1-1500</b>	<i>Tack</i> 1-1.5 Hours (average); <i>Use</i> 3 Hours (light use); <i>Full Cure</i> 5 Days (75° F, 50% RH)

*MicroGuard1® Matte (MG-MT) is formulated be added to MicroGuard1® 1500 where a matte finish is needed. It is designed for installations over hard tile & grout, epoxy terrazzo, slate, decorative stone, concrete, concrete terrazzo, brick-paver, painted metal and non-ferrous metal surfaces. It may be used on horizontal or vertical; interior or exterior installations, wherever resistance to chemicals, water exposure, staining, abrasion, mold mitigation is desired.*

Visit [www.adsil.com](http://www.adsil.com)  
for more information.

Powered by:  
**Adsil**  
CORPORATION